

In a messcall MCS

CWM DH30 (Wall mounted commercial) (45 litres a day)

The CWM DH30, is a wall mounted dehumidifier with a capacity of 45lts per day and is manufactured in the UK. With a PVC coated galvanized steel case, polyester coated evaporator / condenser and compressor delay start timer, this is a quality product. The multi-sensor control circuits provide accurate control and comprehensive unit protection. The standard unit operates to 15C but with hot gas defrost option (X model) they can successfully work at temperatures down to 0C but with reduced capacities. The CWM DH30 is particularly suitable for operation in electrical sub-stations, archives, museums, galleries or libraries, laundry and drying rooms, health and fitness gyms, indoor pools, spas and saunas.



Front profile

Benefits:

- Self contained with fully automatic operations
- Quiet centrifugal fans
- Integral humidistat
- Galvanised steel cabinet

Used in:

- 550 cubic meter commercial environment
- Laundry and drying rooms
- Health & fitness gyms,
- Archives, museums, galleries and libraries
- Indoor pools, spas and saunas

| Specifications | Features |
|---|--|
| Area suitable for | Commercial use – 550 cubic meters |
| Capacity (30C @ 80%RH) | 45.0 lts / day |
| Air circulation | 700 cubic meters / hour |
| Weight | 40 kg |
| Noise level @ 3 mts | 52dB |
| Running cost per day @\$0.19c per KWH | \$0.142 cents/ hr of continuous operation |
| Dimensions H x W x D | 64.8 x 78.2 x 25.6 cm |
| Voltage and power consumption (watts) | 220 – 240 Volts 50Hz / 0.75 kW |
| Permissible room temperature | 15 – 35 degree Celsius / AX model 0 – 35 C |
| Automatic de-icing system | Hot gas defrost for low temperature operations (X model) |
| Refrigerant (CFC free) | R407 |
| Holding tank with overflow protection and tank full indicator | Direct drain only. |
| Direct drainage hose | Condensate drain size is 10mm Inner diameter |
| Warranty | 1 Year (freight not included) |
| Delivery lead time | 6 weeks approximately |
| Other information | Plastisol coated galvanised steel cabinet, mainly white external casing with light grey outside strips. Fully automatic. |